

Daycon Products Company, Inc.
16001 Trade Zone Avenue, Upper Marlboro, MD 20774
Local: (301) 218-1000
Toll Free: (800) 394-0019
Fax: (301) 218-7191

DEEP LUSTRE

High Solids Floor Seal and Finish

Specifications:

Appearance: Opaque liquid
Color: White
Odor: Mild acrylic
Total Solids: 25%
Use Dilution: As is
Coverage (First coat): 1200-1800 sq. ft./gal.
Coverage (Recoating): 1500-2000 sq. ft./gal.
Storage Stability: Two years
minimum in sealed
container
Protective Clothing: See Safety Data
Sheet (SDS)
Coverage: 1500 - 2000 sq. ft. per
gallon
VOC's, % as is: Less than 10
Product Conformance: Manufactured by an
ISO 9001:2015 registered company.

Comment:

Daycon Deep Lustre meets or exceeds C.S.M.A. and U.L. slip resistance standards: of 0.5 minimum as tested by an outside laboratory in accordance with A.S.T.M. -D-2047-82 by a James machine. To maintain high gloss, only neutral cleaners such as Daycon Kleer N' Brite, KBQ-256, KBQ-32, Spectra 4, Spectra 25, Spectra 305, or Spectra 405 should be used in damp mopping or scrubbing. Daycon Maintainer Plus, Sunrise, or Burnishing Gel #27 should be used when burnishing the floor.

Packaging:

Five Gallon Pail
Item Code: DL255GAL
Gallon (4 per case)
Item Code: 336689
55 Gallon Drum
Item Code: DL2555GAL

Date:

February 7, 2018

Description:

Deep Lustre is a high solids, extended wear, scratch and scuff resistant, non-yellowing pure acrylic floor seal and finish. It contains a state-of-the-art highly cross linked polymer that makes it extremely durable, scrubbable, and maintainable with low or ultra high speed floor machines. Because of its high solids, it requires fewer coats, has a high initial shine, and can be easily restored.

Benefits:

- Requires less maintenance than conventional floor finishes
- 25% solids formula requires less coats
- Acrylic polymer resists yellowing with age
- High clarity brings out true color and gloss of floor
- Dries in 20 to 30 minutes
- Easily removed with Daycon Renegade, Meteor, Hurricane, or G-Force

Product Disposal:

This product is non-hazardous material. Dispose of in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

Directions:

1) Prepare the floor, first, by stripping and neutralizing the surface. 2) For best results, use a white, nylon, finishing mop to apply product. Apply one coat of Deep Lustre 25, allowing 20-30 minutes drying time between coats. **DO NOT RECOAT UNTIL THE PREVIOUS COAT IS COMPLETELY DRY.** Buff or burnish to produce a beautiful finish. 3) Maintain with high speed burnishing or low speed buffing. Can dry burnish or use Daycon's Maintainer Plus, Sunrise, Express, or Burnishing Gel #27. To maintain high gloss, only neutral cleaners such as Daycon Kleer N' Brite, KBQ-256, KBQ-32, Spectra 4, Spectra 25, Spectra 305, or Spectra 405 should be used in damp mopping or scrubbing.